

Safety Data Sheet Cover-Sheet – This page provides additional New Zealand specific information for this product, and must be read in conjunction with the safety data sheet attached.

Product Name: **Maxi Temp**

Manufacturer: **Henry Schein**

Accompanying SDS: Henry Schein SDS acc.to (EC) No 1907/2006

Supplier Details: Henry Schein Shalfoon
23 William Pickering Drive, Albany
PO Box 101 140, North Shore, Auckland 0745
Ph. 0800 808 855
www.henryscheinshalfoon.co.nz

Emergency Contacts: Poisons & Hazardous Chemicals Information Centre – 0800 POISON / 0800 764 766
(24-hr)
Phone 111 for Fire, Ambulance or Police

Hazard Identification:

HSNO Classification: Not Applicable Non Hazardous

HSNO Group Standard: Not Applicable Non Hazardous

HSNO Approval Number: Not Applicable Non Hazardous

Hazard Statements: Not Applicable Non Hazardous

Date Prepared: This coversheet prepared 11 May 2016

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Maxi Temp intro & refill

Print date: 11.03.2014

Page 1 of 4

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Maxi Temp HP intro & refill

9001279, 9001280, 9001283, 9002100, 9001281, 9001282, 9001284, 9002126, 9004090

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Manufacturer: Henry Schein Inc. 135 Duryea Road Melville, NY 11747 USA	Authorized EU representative: Henry Schein UK Holdings Ltd. Medcare House, Centurion Close Gillingham Business Park Gillingham, ME8 0SB U.K.	Contact: Tel: +44 (0) 8708 49 08 72 Fax: +44 (0) 1634 87 87 51 cbdeurope@henryschein.com	Emergency #: Chemtrec US: (800) 424-9300 International: 001 703-527-3887
----------------------------------------------------------------------------------------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------	----------------------------------------------------------------------------------------------------------	---------------------------------------------------------------------------------------

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Indications of danger: Xi - Irritant
R phrases:
Irritating to eyes, respiratory system and skin.
May cause sensitisation by skin contact.

GHS classification

Hazard Statements:
May cause respiratory irritation.
Causes serious eye irritation.
Causes skin irritation.
May cause an allergic skin reaction.

2.2. Label elements

Signal word: Warning
Pictograms: GHS07



Hazard statements

H335	May cause respiratory irritation.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.

Precautionary statements

P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P302+P352	IF ON SKIN: Wash with plenty of soap and water.

2.3. Other hazards

No risks worthy of mention. Please observe the information on the safety data sheet at all times.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Maxi Temp intro & refill

Print date: 11.03.2014

Page 2 of 4

Chemical characterization

chemical characterization (preparation): Acrylate.-resin.

SECTION 4: First aid measures

4.1. Description of first aid measures

After inhalation

Exposition vermeiden. Provide fresh air. Move victim to fresh air. Put victim at rest and keep warm.

After contact with skin

After contact with skin, wash immediately with: Water and soap.

After contact with eyes

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

After ingestion

Consult physician.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Water fog. Extinguishing powder. Sand. Foam. Carbon dioxide (CO₂).

Extinguishing media which must not be used for safety reasons

High power water jet.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Provide adequate ventilation.

6.2. Environmental precautions

Do not empty into drains or the aquatic environment.

6.3. Methods and material for containment and cleaning up

Collect mechanically. Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Keep container tightly closed. Wear suitable protective clothing and gloves. Avoid contact with eyes.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place.
Store only in original container.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.2. Exposure controls



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Maxi Temp intro & refill

Print date: 11.03.2014

Page 3 of 4

Protective and hygiene measures

When using do not eat or drink.

Respiratory protection

The following must be prevented: inhalation.

Hand protection

Tested protective gloves are to be worn: Suitable material: NBR (Nitrile rubber).

Eye protection

Tightly sealed safety glasses.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Paste
Colour:	characteristic
Odour:	ester

pH-Value (at 20 °C):	ca. 7	Test method
----------------------	-------	-------------

Changes in the physical state

Boiling point:	>250 °C
point of decomposition:	200 °C
Flash point:	>150 °C
Ignition temperature:	>380 °C
Vapour pressure: (at 20 °C)	1 hPa
Density:	1,5 g/cm ³
Water solubility:	10 g/L
Vapour density:	1

SECTION 10: Stability and reactivity

10.4. Conditions to avoid

heat. Light.
Decomposition takes place from temperatures above: 200 °C
Decomposition under formation of: Acrylate.

10.5. Incompatible materials

radical former. Keep away from strong acids, leachates, heavy metal salts and reducing materials.

10.6. Hazardous decomposition products

Can be released in case of fire: Gas / vapours, irritant. (Acrylate., pungent). nitrogen oxides (NOx).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

LD50: Rat. 5000 mg/kg

Irritation and corrosivity

Frequently or prolonged contact with skin may cause dermal irritation.
Irritant effect on the eye:

Additional information on tests

Contains Methacrylic esters.: May produce an allergic reaction.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Maxi Temp intro & refill

Print date: 11.03.2014

Page 4 of 4

SECTION 12: Ecological information

12.1. Toxicity

Acute fish toxicity LC50: >360 mg/l/48h

12.2. Persistence and degradability

Preparation not tested.

Further information

Do not empty into drains or the aquatic environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Can be burnt together with household waste in compliance with official regulations in contact with approved waste disposal companies and with authorities in charge.

Paste: Carry out a burning of hazardous waste according to official regulations.

Waste disposal number of waste from residues/unused products

180106 WASTES FROM HUMAN OR ANIMAL HEALTH CARE AND/OR RELATED RESEARCH (except kitchen and restaurant wastes not arising from immediate health care); wastes from natal care, diagnosis, treatment or prevention of disease in humans; chemicals consisting of or containing dangerous substances
Classified as hazardous waste.

SECTION 14: Transport information

Other applicable information

Not a hazardous material with respect to these transportation regulations.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulatory information

SECTION 16: Other information

Full text of R phrases referred to under Sections 2 and 3

36/37/38 Irritating to eyes, respiratory system and skin.

43 May cause sensitisation by skin contact.

Full text of H statements referred to under Sections 2 and 3

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)